

Specification Sheet

CONTROL BOX – KDDY104



CATEGORY: FRAME COLUMN FOOT **CONTROL BOX** HANDSET

DESCRIPTION

Control Box, 2 Ports, Battery Powered

PART NUMBER

KDDY104

FEATURES

- Li-ion BATTERY POWERED
- ANTI-COLLISION AND GYRO SENSORS
- PROTECTION AGAINST OVER-CURRENT
- LOW STANDBY POWER CONSUMPTION ($\leq 0.1W$)
- INITIALIZATION
- ERROR CODES

OPTIONS

- 1 OR 2 PORTS
- LIFT SPEED
- SENSOR SENSITIVITY

SPECIFICATIONS	METRIC	ENGLISH
SPEED	$\leq 36MM/S$	$\leq 1.4IN/S$
STROKE	440MM	17.3IN
DIMENSIONS (LXWXH)	130x97x43MM	5.1x3.8x1.7IN
OVERHEATING PROTECTION	-----	-----
VOLTAGE	240VAC/29VDC(BATT)	
OUTPUT	22VDC/8A	
STANDBY POWER	$\leq 0.1W$	
DUTY CYCLE	10%, MAX. 1MIN ON/9MIN OFF	
OVERLOAD PROTECTION	$\geq 6A$	
PROTECTION GRADE	IP20	
UL NUMBER	MH61652	
FLAME CLASS	UL94-V0	
CERTIFICATIONS	UL, CE	
PORTS	2	
MEMORY	BASED ON HANDSET	
COLOR	BLACK	
OPERATING CONDITIONS	RELATIVE HUMIDITY	20%~80% @30°C
	ATMOSPHERIC PRESSURE	700hPa~1060hPa
	AMBIENT TEMPERATURE	+5°C~+40°C (41°F - 104°F)

DIMENSIONS

